

VORT PROMETEO PLUS HR 400

Charakterystyka akustyczna

RPM		Lw dB (A)							Lw dB (A)	Lp dB (A) 3m
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz		
700	Wlot	8.4	9.3	14	22.6	5	9.2	10.1	28	7.5
	Wylot	5.7	15	18.1	16.4	13.9	12.2	7.5	27.5	7
	Emitowane	14.3	39.2	18.3	20.6	2.9	7.1	b.d.	44	23.5
1600	Wlot	18.5	24.1	29.4	37.5	24.8	15.6	13.3	43.2	22.7
	Wylot	16	25.6	27.9	28.4	18.8	6.8	3.3	37.6	17.1
	Emitowane	21.7	31.9	38.3	34	23.8	11.8	7.5	48.4	27.9
2100	Wlot	16.9	32.3	36.6	48.3	35.8	24.7	10.2	56.7	36.2
	Wylot	14.9	34.7	32.8	38.4	29.2	15.7	b.d.	46.4	25.9
	Emitowane	24.6	41.1	41.6	47.1	34.8	20.8	5.6	58	37.5
2650	Wlot	20.3	40.9	46	64.7	41.8	33.7	18.5	65.5	45
	Wylot	19.1	42.5	38.4	60	36	25.6	13.8	60.7	40.2
	Emitowane	31.3	43	48.1	59.2	41.4	29.1	13.6	61.3	40.8
3000	Wlot	23.5	41.3	47.5	52	44.1	37.1	22.8	59.4	38.9
	Wylot	19.7	42.7	40.6	43.2	38	27.1	12.2	53.6	33.1
	Emitowane	28.9	45.7	47.9	47.4	43.9	33.3	16.2	59.5	39
3350	Wlot	25.3	44.4	49.7	54.8	48.4	42.3	28.8	62.7	42.2
	Wylot	23.6	43.4	43.2	45.7	41.5	31.6	13.5	55.5	35
	Emitowane	31.8	46.7	51.5	55.2	47.5	37.4	22	62.4	41.9